
Printed by EAST

UserID: SAzarian

Computer: WS08483

Date: 02/08/2004

Time: 17:31

| | Type | L # | Hits | Search Text | DBs | Time Stamp |
|---|------|-----|--------|---|-------|------------------|
| 1 | BRS | L1 | 142868 | ((image or images or target\$3 or motion) with (detection or detecting or detect\$3 or track\$4)) | USPAT | 2004/02/08 17:29 |
| 2 | BRS | L2 | 9848 | 1 and adder | USPAT | 2004/02/08 17:30 |
| 3 | BRS | L3 | 4110 | 2 and ((convert\$5 or change\$3) with (signal or signals) with (digital\$2)) | USPAT | 2004/02/08 17:27 |
| 4 | BRS | L4 | 297 | 3 and photodetect\$4 | USPAT | 2004/02/08 17:28 |
| 5 | BRS | L5 | 177 | 4 and clock\$4 | USPAT | 2004/02/08 17:29 |
| 6 | BRS | L6 | 111 | 5 and ((image or images or target\$4) with (detection or detecting or detect\$5)) | USPAT | 2004/02/08 17:30 |
| 7 | BRS | L7 | 34 | 6 and ((first or second) with (adder)) | USPAT | 2004/02/08 17:31 |

| | Comments | Error Definition | Errors |
|---|----------|------------------|--------|
| 1 | | | 0 |
| 2 | | | 0 |
| 3 | | | 0 |
| 4 | | | 0 |
| 5 | | | 0 |
| 6 | | | 0 |
| 7 | | | 0 |

| | Title | Current OR | Current XRef | Retrieval Classif |
|----|--|------------|---|-------------------|
| 1 | Method and apparatus for improved estimation of characteristics of pulses detected by a nuclear camera | 250/369 | 250/363.07 | |
| 2 | Optical disc tilt control apparatus | 369/44.32 | 369/44.28; 369/44.35; 369/53.19 | |
| 3 | Method for acquiring measurements and scanner implementing said method | 378/17 | 378/4; 378/901 | |
| 4 | Method for acquiring measurements and scanner with sensor groups | 378/19 | 378/15; 378/901 | |
| 5 | Optical disc and optical disc driving device | 369/59.14 | 369/116; 369/13.26; 369/47.52; 369/53.26; 369/53.37 | |
| 6 | Optical disc and optical disc driving device | 369/53.41 | 369/53.2; 369/59.23 | |
| 7 | Optical storage apparatus | 369/44.28 | 369/44.29; 369/44.34; 369/44.35 | |
| 8 | Recording apparatus having a partially exchangeable disk array, a loading/unloading device, and a control device and which uses a disk-like recording medium | 711/114 | 369/30.4; 369/32.01; 714/6 | |
| 9 | Optical disc and optical disc driving device | 369/275.3 | 369/275.1 | |
| 10 | Apparatus and method of rapidly locating edges of machine-readable symbols or other linear images | 235/462.12 | 235/462.1; 235/462.25; 235/462.41; 382/199; 382/296 | |
| 11 | Apparatus for recording magneto-optic disks | 711/114 | 369/30.34 | |
| 12 | Distance measuring apparatus | 356/5.01 | 327/72; 342/135 | |
| 13 | Method and apparatus for non-contact reading of a relief pattern | 235/454 | 235/462.42; 235/462.45; 235/494; 382/218; 382/292 | |
| 14 | Symbol scanning system and method having adaptive pattern generation | 235/462.25 | 235/470 | |

| | Title | Current OR | Current XRef | Retrieval Classif |
|----|---|------------|---|-------------------|
| 15 | High fidelity reproduction device for cinema sound | 352/31 | 352/12; 352/20; 352/25; 352/5; 352/92 | |
| 16 | Solid state image sensing device | 348/230.1 | 348/297 | |
| 17 | Spatial filter for an image processing system | 382/132 | 382/260 | |
| 18 | Optical information recording reproducing apparatus for recording and reproducing information on a record medium and for generating track error signals | 369/44.11 | 235/454; 369/44.26; 369/53.29 | |
| 19 | Track jump control apparatus | 369/44.28 | 360/78.07; 369/30.15 | |
| 20 | Optical record medium reading apparatus having a de-focussed light beam projected on an optical record medium | 369/44.32 | 235/456; 369/116; 369/118; 369/44.35; 369/44.42; 369/53.15 | |
| 21 | Real time registration weave correction system | 386/130 | 348/103; 348/263 | |
| 22 | Read-out photodiodes using sigma-delta oversampled analog-to-digital converters | 341/143 | 378/19 | |
| 23 | Process of correction of signals from a linear radiation detector and correction device using this process | 250/208.1 | 382/254 | |
| 24 | Image recording apparatus for producing a plurality of pulse width modulated signals on the basis of image data | 347/252 | 358/296 | |
| 25 | Color image processing method | 358/512 | 348/265 | |
| 26 | Image pick-up apparatus | 250/201.4 | 250/226; 358/481; 358/494; 358/505; 359/206; 359/215 | |
| 27 | Infrared thermography system with sensitivity improved by progressive accumulation of image lines | 348/164 | 250/334; 348/125 | |

| | Title | Current OR | Current XRef | Retrieval Classif |
|----|--|------------|---|-------------------|
| 28 | Alignment apparatus | 356/401 | 356/153; 356/400 | |
| 29 | Automatic focusing apparatus | 396/127 | 250/204; 396/128 | |
| 30 | Circuit arrangement for crosstalk compensation in electro-optical scanners | 348/248 | | |
| 31 | Automatic exposure control for automatic-focus cameras | 396/119 | 396/233 | |
| 32 | Photographic camera | 396/110 | 396/233 | |
| 33 | Focussing system | 396/119 | 250/201.8; 250/214B; 352/140; 356/3.15 | |
| 34 | Automatic focus control for a microscope | 250/204 | 348/353; 348/79 | |